

Extra Heavy Duty Castors



5000 Series (Swivel)




Size: 160mm & 200mm

5050 Series (Fixed)

Size: 160mm & 200mm

Very heavy duty swivel and fixed castors. Suitable for a wide range of industrial applications. Available with rubber, polyurethane, nylon and cast iron wheels.

Castor Reference and Load Capacity

Wheel Diam.	Tread width (mm)	Castor Type	Castor Height	Plate size (mm)	Bolt Hole spacin' (mm)	Bolt Diam.	Swiv. Rad.				
								Rubber	Polyurethane	White Nylon	Cast Iron
5" 125mm	HRT=50 SUB=50 NYB=50	Swivel	164mm	140 x 110	105 x 80/75	10mm	118mm	125-5000- HRT 300kg	125-5000-SUB 550kg	125-5000-NYB 700kg	-
		Fixed	164mm	140 x 110	105 x 80/75	10mm	-	125-5050- HRT 300kg	125-5050-SUB 550kg	125-5050-NYB 700kg	-
6" + 160mm	HRT=50 SUB=50 NYB=50 CIB=45	Swivel	*200mm	140 x 110	105 x 80/75	10mm	135mm	160-5000- HRT 400kg	160-5000-SUB 700kg	160-5000-NYB 700kg	150-5000-CIB 700kg
		Fixed	*200mm	140 x 110	105 x 80/75	10mm	-	160-5050- HRT 400kg	160-5050-SUB 700kg	160-5050-NYB 700kg	150-5050-CIB 700kg
8" 200mm	HRT=50 SUB=50 NYB=50 CIB=45	Swivel	240mm	140x 110	105 x 80/75	10mm	155mm	200-5000- HRT 500kg	200-5000-SUB 800kg	200-5000-NYB 800kg	200-5000-CIB 800kg
		Fixed	240mm	140 x 110	105 x 80/75	10mm	-	200-5050- HRT 500kg	200-5050-SUB 800kg	200-5050-NYB 800kg	200-5050-CIB 800kg

*When the 6" cast iron wheels are used, the castor height is reduced by 10mm.

OPTIONAL EXTRAS

Combined Swivel and Wheel Brake



Foot operated wheel brake simultaneously brakes both the swivel head and wheel. Release is affected by the trip pedal. To order add suffix 'SWB' to the swivel castor reference.

Swivel Radius

The swivel radius is increased when brakes are fitted.
125mm wheels: increased by 30mm
160mm wheels: increased by 15mm
The 6" cast iron wheels are not available with brakes.

TLCH Truck Locks



Top plate fitting

The TLCH truck lock is designed to bolt to the underside of the truck and should be mounted with its top face 200mm above the ground surface.

Plate size	Bolt Hole Spacing	Bolt Diam.	Overall height - free position	Overall height - pad extended
152 x 114mm	127 x 63.5mm	12mm	163.5mm	208mm