

# Medium/Heavy Duty Castors

## 3360 Series (Swivel)

Size: 80mm, 100mm, 125mm, 160mm & 200mm



## 3368 Series (Fixed)

Size: 80mm, 100mm, 125mm, 160mm & 200mm

Double Ball Bearing Swivel & Fixed Castors.

The castors are suitable for use on trolleys, roll pallets, display racks and general purpose equipment where good manoeuvrability and easy rolling is required together with high strength. Available with rubber, polyurethane or nylon wheels.

8mm bolt diameter for 3", 4" and 5" castors. The 6" and 8" castors have 10mm bolt diameters

### Castor Reference and Load Capacity

Wheel Diam.	Tread width (mm)	Castor Type	Castor Height	Plate size	Bolt Hole spacin'	Swiv. Rad.	Blue Rubber	Grey Rubber	Black Rubber	Polyurethane	PB White Nylon	RB White Nylon
3" + 80mm	RN=36 GV=27 PV=27 PN=38 NY=34	Swivel	108mm	105 x 85mm	80 x 60mm	75mm	80-3360-RNB 90kg	80-3360-GVR 70kg	80-3360-PVR 70kg	*80-3360-PNB 150kg	80-3360-NY 150kg	-
		Fixed	108mm	99 x 85mm	80 x 60mm	-	80-3368-RNB 90kg	80-3368-GVR 70kg	80-3368-PVR 70kg	*80-3368-PNB 150kg	80-3368-NY 150kg	-
4" 100mm	RN=29 GV=23 PV=23 PN=30 NY=34	Swivel	128mm	105 x 85mm	80 x 60mm	85mm	100-3360-RNB 160kg	100-3360-GVR 80kg	100-3360-PVR 80kg	100-3360-PNB 200kg	-	100-3360-NYB 200kg
		Fixed	128mm	101 x 85mm	80 x 60mm	-	100-3368-RNB 160kg	100-3368-GVR 80kg	100-3368-PVR 80kg	100-3368-PNB 200kg	-	100-3368-NYB 200kg
5" 125mm	RN=34 GV=23 PV=23 PN=30 NY=38	Swivel	155mm	105 x 85mm	80 x 60mm	105mm	125-3360-RNB 180kg	125-3360-GVR 100kg	**125-3360-PVR 100kg	125-3360-PNB 250kg	-	125-3360-NYB 300kg
		Fixed	155mm	101 x 85mm	80 x 60mm	-	125-3368-RNB 180kg	125-3368-GVR 100kg	**125-3368-PVR 100kg	125-3368-PNB 250kg	-	125-3368-NYB 300kg
6" + 160mm	RN=40 GV=25 PV=25 PN=40 NY=40	Swivel	200mm	137 x 105mm	105 x 80mm	140mm	160-3360-RNB 300kg	160-3360-GVR 150kg	**160-3360-PVR 150kg	160-3360-PNB 300kg	160-3360-NY 350kg	160-3360-NYB 350kg
		Fixed	200mm	137 x 115mm	105x 80mm	-	160-3368-RNB 300kg	160-3368-GVR 150kg	**160-3368-PVR 150kg	160-3368-PNB 300kg	160-3368-NY 350kg	160-3368-NYB 350kg
8" 200mm	RN=40 GV=33 PV=33 PN=50 NY=46	Swivel	240mm	137 x 105mm	105x 80mm	165mm	200-3360-RNB 400kg	200-3360-GVR 200kg	**200-3360-PVR 200kg	200-3360-PNB 400kg	200-3360-NY 400kg	200-3360-NYB 400kg
		Fixed	240mm	137 x 115mm	105 x 80mm	-	200-3368-RNB 400kg	200-3368-GVR 200kg	**200-3368-PVR 200kg	200-3368-PNB 400kg	200-3368-NY 400kg	200-3368-NYB 400kg

\*The 80mm Polyurethane wheel is grey on grey. \*\* The 125mm, 160mm & 200mm Black Rubber Wheels have red centres.

## OPTIONAL EXTRAS

### Combined Swivel and Wheel Brake (all sizes)

Foot operated wheel brake simultaneously brakes both the swivel head and wheel. Release is affected by the trip pedal. To order add suffix 'SWB' to the swivel castor reference.

#### Swivel Radius

The swivel radius is increased when brakes are fitted.

80mm wheels: increased by 45mm  
100mm wheels: increased by 40mm  
125mm wheels: increased by 30mm  
160mm wheels: increased by 30mm  
200mm wheels: increased by 20mm



### Directional Swivel Locks

Loose fitted (unassembled) directional swivel locks available on 6" and 8" castors.

