

Pneumatic & Trolley Wheels



PD Series

Wheel Diameter	Tread Width	Load Cap.	Hub Length	Hub Bore	Reference Plain
6" (150mm)	39mm	30kg	38mm	1/2"	PD-6
7" (180mm)	45mm	50kg	38mm	1/2"	PD-7
8" (200mm)	45mm	50kg	38mm	1/2"	PD-8

"Light duty wheels - tough moulded polypropylene centres fitted with ribbed tyres. PD range is specially designed for grass cutting machines and other light horticultural applications."



ABC Series

Wheel Diameter	Tread Width	Load Cap.	Hub Length	Hub Bore	Reference Plain
80mm	21mm	30kg	37mm	8mm	A-80
100mm	24mm	35kg	35mm	10mm	A-100
125mm	31mm	50kg	44mm	15mm	A-125
160mm	40mm	100kg	44mm	20mm	AB-160
200mm	33mm	130kg	44mm	20mm	AB-200L

"Traditional light industrial range of wheels. The centres are black polypropylene with black rubber tyres."



EPR Series

Wheel Diameter	Tread Width	Load Cap.	Hub Length	Hub Bore	Reference Plain
6" (160mm)	30mm	150kg	51mm	3/4"	EPR-6 (3/4")
6" (160mm)	30mm	150kg	51mm	1"	EPR-6 (1")
8" (200mm)	30mm	200kg	51mm	3/4"	EPR-8 (3/4")
8" (200mm)	30mm	200kg	51mm	1"	EPR-8 (1")
10" (250mm)	60mm	275kg	51mm	1"	EPR-10 (1")
11" (270mm)	60mm	150kg	59mm	1"	EPR-11 (1")

"Light industrial range of cushion tyred wheels having red centres with black tyres. Ideally suited for sack trucks and trolleys etc. Alternative diameters and hub bores available."

We can produce bushes for the hub bore, which will reduce the bore size to: 1/2" or 20mm. The hub lengths will then be increased by 8mm and the load capacity reduced by 50%.



GB Series (Sandhopper)

Wheel Diameter	Tread Width	Load Cap.	Hub Length	Hub Bore	Reference Plain
10 5/8" (270mm)	98mm	125kg	56mm	1"	GB-270 (1")

"Extra wide tread wheels. Suitable for barrows, launching trolleys and any outdoor application."

We can produce bushes for the hub bore, which will reduce the bore size to: 1/2" or 20mm. The hub lengths will then be increased by 8mm and the load capacity reduced by 50%.



PW Series (Plastic Centres)

Wheel Diameter	Tread Width	Load Cap.	Hub Length	Hub Bore	Wheel Reference
8 3/4" (220mm)	65mm	100kg	76mm	1"PB	PW-250-4-25.4-76
10 1/4" (260mm)	85mm	120kg	76mm	1"PB	PW-300-4-25.4-76
10 1/4" (260mm)	85mm	120kg	76mm	1"RB	PWR-300-4-25.4-76
16" (400mm)	100mm	150kg	68mm	1"PB	PW-400-8-25.4-68
16" (400mm)	100mm	150kg	75mm	1"RB	PWR-400-8-25.4-75

"Pneumatic tyred wheels suitable for low speed applications. Red centres with black tyres 4 ply rating."

We can produce bushes for the hub bore, which will reduce the bore size to: 1/2" or 20mm. The hub lengths will then be increased by 8mm and the load capacity reduced by 50%.



PW Series (Plastic Centres)

Wheel Diameter	Tread Width	Load Cap.	Hub Length	Hub Bore	Wheel Reference
10 1/4" (260mm)	85mm	120Kg	75mm	20mm RB	PWR-250-4-20-76/PP
10 1/4" (260mm)	85mm	120Kg	75mm	1" RB	PWR-250-4-25.4-76/PP
16" (400mm)	105mm	180Kg	75mm	20mm RB	PWR-400-4-20-75/PP
16" (400mm)	105mm	180Kg	75mm	1" RB	PWR-400-4-25.4-75/PP

"Black, puncture-proof lightweight micro-cellular polyurethane tyre on red polypropylene centre"

We can produce bushes for the hub bore, which will reduce the bore size to: 1/2" or 20mm. The hub lengths will then be increased by 8mm and the load capacity reduced by 50%.



PW Series (Metal Centres)

Wheel Diameter	Tread Width	Load Cap.	Hub Length	Hub Bore	Reference Plain
8" (200mm)	48mm	75kg	60mm	20mm	WAT-8RBM20
10 1/4" (260mm)	85mm	200kg	76mm	20mm	PWMR-300-4-20-76
10 1/4" (260mm)	85mm	200kg	76mm	1"RB	PWMR-300-4-25.4-76
*16" (400mm)	100mm	250kg	76mm	1"RB	PWMR-400-8-25.4-76

"Pneumatic tyred wheels suitable for low speed applications. Grey Metal centres with black tyres 4 ply rating."

* The 16" diameter wheel has a red metal centre and is also available in black to special order.